

ADAPTIVE ENERGY MINIMISATION FOR hp -FINITE ELEMENT METHODS

PAUL HOUSTON AND THOMAS P. WIHLE

ABSTRACT. This article is concerned with the numerical solution of convex variational problems. More precisely, we develop an iterative minimisation technique which allows for the successive enrichment of an underlying discrete approximation space in an adaptive manner. Specifically, we outline a new approach in the context of hp -adaptive finite element methods employed for the efficient numerical solution of linear and nonlinear second-order boundary value problems. Numerical experiments are presented which highlight the practical performance of this new hp -refinement technique for both one- and two-dimensional problems.

1. INTRODUCTION

Over the last few decades, tremendous progress has been made on both the mathematical analysis and practical application of finite element methods to a wide range of problems of industrial importance. In particular, significant contributions have been made in the area of *a posteriori* error estimation and automatic mesh adaptation. For recent surveys and historical background, we refer to [2, 11, 18, 21, 34, 36], and the references cited therein. Here, adaptive methods seek to automatically enrich the underlying finite element space, from which the numerical solution is sought, in order to compute efficient and reliable numerical approximations. The standard approach used within much of the literature is to simply undertake local isotropic refinement of the elements (h -refinement). However, in recent years, so-called hp -adaptive finite element methods have been devised, whereby both local subdivision of the elements and local polynomial-degree-variation (p -refinement) are employed. These ideas date back to the work by Babuška and co-workers (cf. [7–10]); see also the recent books [14, 24, 32, 33], and the references cited therein. The exploitation of general hp -refinement strategies can produce remarkably efficient methods with high algebraic or even exponential rates of convergence. Moreover, such approaches can also be combined with anisotropic refinement techniques in order to efficiently approximate problems with sharp transition features. These techniques enable the user to perform accurate and reliable computational simulations without excessive computing resources, and with the confidence that complex local features of the underlying solution are accurately captured.

Many physical processes can be modelled by locating critical points of a given (in our setting, convex) energy functional, over an admissible space of functions; a

2010 *Mathematics Subject Classification.* 65N30.

Key words and phrases. Convex variational problems, hp -finite element methods, hp -adaptivity, quasilinear partial differential equations.

PH acknowledges the financial support of the Leverhulme Trust.

TW acknowledges the financial support by the Swiss National Science Foundation (SNF).

typical example includes quasilinear partial differential equations (PDEs). In this article we consider the application of adaptive finite element techniques, employing a combination of hp -mesh refinement, to problems of this type. In particular, we consider a new and widely applicable paradigm for adaptive mesh generation within which we directly seek to construct the hp -finite element space in order to approximate the critical point of the underlying energy functional associated to the problem of interest. The simplest such example is the one-dimensional Poisson equation on the interval $(0, 1)$, subject to a load f ; in this case, we seek to minimise $E(u) = 1/2 \int_0^1 u_x^2 dx - \int_0^1 f u dx$ over an appropriate solution space V (which naturally incorporates the boundary conditions). The corresponding standard Galerkin finite element approximation of this problem automatically inherits the same energy minimisation property with respect to the underlying finite element space $V_h \subset V$, i.e., the finite element solution is the unique minimiser of $E(\cdot)$ over V_h . With this idea in mind, a natural approach is to adaptively modify the finite element space V_h in a manner which seeks to directly decrease the energy E , i.e., denoting the new finite element solution and finite element space by u'_h and V'_h , respectively, we require that $E(u'_h) \leq E(u_h)$. By considering an appropriately defined elementwise energy functional \tilde{E}'_κ , with κ denoting the current element in the underlying computational mesh, we devise a competitive refinement strategy which marks elements for refinement. More precisely, in the context of our one-dimensional example, consider an h -refinement strategy which subdivides each element into two sub-elements. We may then compute the numerical solution to a local finite element problem posed on a local patch of elements which includes the two sub-elements. On the basis of this local reference approximation, we may then determine the predicted (elemental) energy loss if the proposed refinement (i.e., a bisection of each element into two sub-elements) is undertaken. Once the predicted energy loss has been computed for all elements in the mesh, a percentage of elements with the largest predicted energy loss may be identified and subsequently refined. This idea naturally extends to the p -refinement setting, whereby, additional higher-order modes are used to locally enrich the finite element solution elementwise. With this in mind, we propose a competitive hp -adaptive refinement strategy which computes the maximal predicted energy loss on each element based on comparing a p -refinement of each element (i.e., an isotropic increase of the elemental polynomial degrees by 1) with a collection of h -refinements of the same element (featuring different local polynomial degree distributions), which are selected so as to lead to the same increase in the number of degrees of freedom associated with the current element as the p -enrichment, cf. [14, 15, 29, 31, 33]. A key aspect of this algorithm is the computation of a local elementwise/patchwise reference solution needed for the definition of \tilde{E}'_κ . In order to illustrate the key ideas, for the purposes of this article, we restrict our discussion to convex optimisation problems posed on a computational domain $\Omega \subset \mathbb{R}^d$, $d \geq 1$. However, we point out that this strategy is completely general in the sense that it can be applied to any physical problem which may be modelled as a critical point of a given energy functional E (including saddle point problems, see, e.g., [30]). In particular, one of the key advantages of our proposed approach is that it naturally facilitates the use of hp -mesh adaptation, and indeed even anisotropic hp -mesh refinement. By considering an enrichment of the finite element space locally using any combination of isotropic/anisotropic h -/ p -refinement, an element κ can be refined according to the refinement which

leads to the maximal predicted energy loss. This is in contrast to standard adaptive techniques, whereby elements are marked for refinement according to the size of a local *a posteriori* error indicator. Indeed, in this latter setting, such indicators rarely contain information concerning how the local finite element space should be enriched, but only indicate that a refinement should be performed. Thereby, alternative numerical techniques must be devised which are capable of determining the direction of refinement (for anisotropic refinement) or the type of refinement (*h*- or *p*-). For the latter case, such strategies include regularity estimation [17, 22, 25, 37], use of *a priori* knowledge [12, 35], and the computation of reference solutions within competitive refinement strategies [3, 14, 16, 19, 20, 26, 28, 29, 31, 33], for example. This latter class of methods, cf. in particular [14, 15, 29, 31, 33] and [19, 20], are very much in the spirit of the proposed competitive refinement algorithm developed in this article. Finally, we refer to [27] for an extensive review and comparison of many of the *hp*-adaptive refinement techniques proposed within the literature.

This article is structured as follows. In Section 2 we briefly present an abstract framework for variational problems, and consider an application to quasilinear partial differential equations. Subsequently, in Section 3, the *hp*-version finite element discretisation of such problems is presented, and a new *hp*-adaptivity approach is developed in detail. The theory will be illustrated with a number of numerical experiments on linear and quasilinear boundary value problems in Section 5. Finally, in Section 6 we summarise the work presented in this article and draw some conclusions.

Throughout this article, we let $L^p(D)$, $p \in [1, \infty]$, be the standard Lebesgue space on some bounded domain D , with boundary ∂D , equipped with the norm $\|\cdot\|_{L^p(D)}$. Furthermore, for $k \in \mathbb{N}$, we write $W^{k,p}(D)$ to signify the Sobolev space of order k , endowed with the norm $\|\cdot\|_{W^{k,p}(D)}$ and seminorm $|\cdot|_{W^{k,p}(D)}$. For $p = 2$ we write $H^k(D)$ in lieu of $W^{k,2}(D)$; moreover, $H_0^1(D)$ denotes the subspace of $H^1(D)$ of functions with zero trace on ∂D .

2. VARIATIONAL PROBLEMS

In this section we outline an abstract framework for variational problems in Banach spaces, and consider an application to quasilinear boundary value problems.

2.1. Abstract Minimisation Problem. On a real reflexive Banach space X let us consider the minimisation problem

$$(2.1) \quad \min_{u \in X} E(u) \equiv \min_{u \in X} \{F(u) - \langle l, u \rangle\}.$$

Here, $\langle \cdot, \cdot \rangle$ is the duality product on $X \times X'$, where X' signifies the dual space of X , and $l \in X'$ is given. Furthermore, throughout this manuscript, we suppose that $F : X \rightarrow \mathbb{R}$ is a continuous and strictly convex functional on X , i.e.,

$$F(v_1 + t(v_2 - v_1)) < F(v_1) + t(F(v_2) - F(v_1)) \quad \forall t \in [0, 1] \quad \forall v_1, v_2 \in X.$$

In addition, we make the assumption that F satisfies the coercivity type condition

$$F(u) - \langle l, u \rangle \rightarrow +\infty \quad \text{as } \|u\|_X \rightarrow \infty,$$

where $\|\cdot\|_X$ is a norm on X . Then, (2.1) possesses a unique minimiser $u^* \in X$; see, e.g., [38, Corollary 42.14]. Furthermore, the problem of finding $u^* \in X$ can be written in weak form as

$$\langle F'(u^*), v \rangle = \langle l, v \rangle \quad \forall v \in X,$$

provided that F has a sufficiently regular Gâteaux derivative F' .

2.2. Model Problem. We now consider a specific application of the above abstract setting. To this end, let $\Omega \subset \mathbb{R}^d$, $d \geq 1$, be an open bounded Lipschitz domain with boundary $\partial\Omega$. We consider the following quasilinear partial differential equation:

$$(2.2) \quad \begin{aligned} -\nabla \cdot (\mu'(\nabla u^*)) + g'(u^*) &= f, & \text{in } \Omega, \\ u^* &= 0, & \text{on } \partial\Omega. \end{aligned}$$

Here, $f = f(x)$, $\mu = \mu(\nabla u)$, and $g = g(u)$ are given functions, and $u^* = u^*(x)$ is the unknown analytical solution. We suppose that $f \in L^q(\Omega)$, for some $q > 1$. The corresponding variational problem reads:

$$(2.3) \quad \min_{u \in X} E(u) := \min_{u \in X} \int_{\Omega} \{\mu(\nabla u) + g(u) - fu\} \, dx,$$

where $X = W_0^{1,p}(\Omega)$ for some suitable $p > 1$.

With this notation, the following proposition, which can be established along the lines of the proof of [38, Example 42.15, Part I], holds true.

Proposition 2.4. *Let μ and g from (2.3) be strictly convex and convex, respectively, and both continuous on \mathbb{R}^d and \mathbb{R} , respectively. Furthermore, suppose that, for some constants $C_1, C_2 > 0$, $p > 1$, and $c_1, c_2 \in \mathbb{R}$ the lower bounds hold,*

$$\mu(\xi) \geq C_1 |\xi|^p, \quad g(\eta) \geq c_1 \eta + c_2,$$

as well as the growth conditions

$$\mu(\xi) \leq C_2(1 + |\xi|^p), \quad g(\eta) \leq C_2(1 + |\eta|^p),$$

for any $\xi \in \mathbb{R}^d$, and any $\eta \in \mathbb{R}$. Then, for any given $f \in L^q(\Omega)$, where $1/p + 1/q = 1$, (2.3) has a unique solution in $X = W_0^{1,p}(\Omega)$ as well as on any linear subspace of X .

3. hp -FINITE ELEMENT DISCRETISATION

Consider now a linear subspace $X_n \subset X$ with $\dim(X_n) = n < \infty$. Then, by our previous assumptions on F , solving the finite dimensional convex optimisation problem $\min_{u \in X_n} E(u)$ for the unique minimiser $u_n^* \in X_n$ results in an approximation of $u^* \in X$ from (2.1) with $u_n^* \approx u^*$. This is the well-known Ritz method. Equivalently, in weak form, we may seek $u_n^* \in X_n$ such that the Galerkin formulation

$$\langle F'(u_n^*), v \rangle = \langle l, v \rangle \quad \forall v \in X_n$$

is satisfied; cf. [38, § 42.5].

For the purposes of discretising our model problem (2.2), we will focus on an hp -finite element approach. To this end, let us first introduce some notation: We let $\mathcal{T} = \{\kappa\}$ be a subdivision of the computational domain Ω into disjoint open simplices such that $\bar{\Omega} = \bigcup_{\kappa \in \mathcal{T}} \bar{\kappa}$ and denote by h_κ the diameter of $\kappa \in \mathcal{T}$; i.e., $h_\kappa = \text{diam}(\kappa)$. In addition, to each element $\kappa \in \mathcal{T}$ we associate a polynomial degree p_κ , $p_\kappa \geq 1$, and collect the p_κ in the polynomial degree vector $\mathbf{p} = [p_\kappa : \kappa \in \mathcal{T}]$. With this notation we define the hp -finite element spaces by

$$\begin{aligned} \mathcal{V}(\mathcal{T}, \mathbf{p}) &= \{v \in H^1(\Omega) : v|_\kappa \in \mathbb{P}_{p_\kappa}(\kappa) \, \forall \kappa \in \mathcal{T}\}, \\ \mathcal{V}_0(\mathcal{T}, \mathbf{p}) &= \mathcal{V}(\mathcal{T}, \mathbf{p}) \cap H_0^1(\Omega), \end{aligned}$$

where, for $p \geq 1$, we denote by $\mathbb{P}_p(\kappa)$ the space of polynomials of total degree p on κ .

The hp -version finite element approximation of the variational formulation (2.1) is given by: Find the numerical approximation $u_{\text{hp}}^* \in \mathcal{V}_0(\mathcal{T}, \mathbf{p})$ such that

$$\mathbf{E}(u_{\text{hp}}^*) = \min_{u \in \mathcal{V}_0(\mathcal{T}, \mathbf{p})} \mathbf{E}(u),$$

where \mathbf{E} is defined in (2.3), or equivalently, provided that the (weak) derivatives μ' and g' belong to $L_{\text{loc}}^1(\Omega)$, in weak form: Find $u_{\text{hp}}^* \in \mathcal{V}_0(\mathcal{T}, \mathbf{p})$ such that

$$(3.1) \quad a_{\Omega}(u_{\text{hp}}^*, v) = \ell_{\Omega}(v) \quad \forall v \in \mathcal{V}_0(\mathcal{T}, \mathbf{p}).$$

Here,

$$\begin{aligned} a_{\Omega}(w, v) &:= \int_{\Omega} \{\mu'(\nabla w) \cdot \nabla v + g'(w)v\} \, dx, & w, v \in \mathcal{V}(\mathcal{T}, \mathbf{p}), \\ \ell_{\Omega}(v) &:= \int_{\Omega} f v \, dx, & v \in \mathcal{V}(\mathcal{T}, \mathbf{p}). \end{aligned}$$

This is the hp -finite element discretisation of (2.2).

4. hp -ADAPTIVITY

The goal of this section is to design a procedure that generates sequences of hp -adaptively refined finite element spaces in such a manner as to minimise the error in the computed energy functional \mathbf{E} . In the context of hp -version finite element methods, the *local* finite element space on a given element κ , $\kappa \in \mathcal{T}$, may be enriched in a number of ways. In particular, traditional hp -adaptive finite element methods typically make a choice between either:

- p -refinement: The local polynomial degree p_{κ} on κ is increased by a given increment, p_{inc} : $p_{\kappa} \leftarrow p_{\kappa} + p_{\text{inc}}$. Typically, a value of $p_{\text{inc}} = 1$ is selected.
- h -refinement: The element κ is divided into a set of n_{κ} new sub-elements, such that $\bar{\kappa} = \bigcup_{i=1}^{n_{\kappa}} \bar{\kappa}_i$. Here, n_{κ} will depend on both the type of element to be refined, and the type of refinement employed, i.e., isotropic/anisotropic. For isotropic refinement of a triangular element κ in two-dimensions, we have $n_{\kappa} = 4$. The polynomial degree may then be inherited from the parent element κ , i.e., we set $p_{\kappa_i} = p_{\kappa}$, for $i = 1, \dots, n_{\kappa}$.

Motivated by the work presented in [31], cf. also [14, 15, 29, 33], for example, in this article, we consider a competitive refinement strategy, whereby on each element κ in \mathcal{T} , we estimate the predicted reduction in the *local contribution* to the energy functional \mathbf{E} based on either employing p -refinement, with $p_{\text{inc}} = 1$, together with a series of hp -refinements, which lead to the same number of degrees of freedom as the p -enrichment. In contrast to standard h -refinement, where the subdivided elements inherit the polynomial degree of their parent, cf. above, in this latter case, the distribution of the polynomial degrees on the resulting sub-elements is possibly non-uniform.

4.1. Motivation. The key to the forthcoming hp -refinement strategy is to estimate the predicted reduction in the energy functional locally on each element in the finite element mesh \mathcal{T} . With this in mind, we must first rewrite \mathbf{E} as the sum

of local contributions on \mathcal{T} . Given that \mathbf{E} is simply defined as an integral over Ω , then clearly, we may write

$$\mathbf{E}(v) = \sum_{\kappa \in \mathcal{T}} \mathbf{E}_\kappa(v),$$

where \mathbf{E}_κ is defined in an analogous fashion to \mathbf{E} , with the integrals over Ω being restricted to integrals over κ , $\kappa \in \mathcal{T}$.

However, while the above definition of the local energy functionals \mathbf{E}_κ seems entirely natural, there is no guarantee that the computed error will converge optimally based on locally minimising \mathbf{E}_κ over each κ in \mathcal{T} . In order to investigate this issue further and to motivate the idea proposed in this article, let us consider the following second-order linear self-adjoint partial differential equation: Find u^* such that

$$(4.1) \quad -\Delta u^* + u^* = f \quad \text{in } \Omega, \quad u^* = 0 \quad \text{on } \partial\Omega.$$

Thereby, we have that

$$(4.2) \quad \mu(\nabla u) = \frac{1}{2} |\nabla u|^2, \quad g(u) = \frac{1}{2} u^2,$$

and $X = H_0^1(\Omega)$ (i.e., $p = q = 2$). In this setting, the (global) energy functional from (2.3) may be written in the form

$$\mathbf{E}(u) = \frac{1}{2} a_\Omega(u, u) - \ell_\Omega(u).$$

Moreover, we may define the associated energy norm: $\|u\|_{\mathbf{E}}^2 := a_\Omega(u, u)$. Given the energy norm, exploiting the symmetry of the bilinear form $a_\Omega(\cdot, \cdot)$, we immediately deduce the following relationship between the error in the computed energy functional \mathbf{E} , and the error measured in terms of the energy norm $\|\cdot\|_{\mathbf{E}}$, namely:

$$\mathbf{E}(u^*) - \mathbf{E}(u_{\text{hp}}^*) = -\frac{1}{2} \|u^* - u_{\text{hp}}^*\|_{\mathbf{E}}^2.$$

Thereby, on a global level, reduction of the error in the energy functional \mathbf{E} naturally leads to a reduction in the energy norm of the error.

In order to repeat this argument on a subset $\mathcal{D} \subset \Omega$, we now suppose that the boundary datum g is given and seek $u^* \in H^1(\mathcal{D})$ such that $u^*|_{\partial\mathcal{D}} = g$ and

$$(4.3) \quad a_{\mathcal{D}}(u^*, v) = \ell_{\mathcal{D}}(v) \quad \forall v \in H_0^1(\mathcal{D}).$$

Here, $a_{\mathcal{D}}(\cdot, \cdot)$ and $\ell_{\mathcal{D}}(\cdot)$ are defined in an analogous manner to $a_\Omega(\cdot, \cdot)$ and $\ell_\Omega(\cdot)$, respectively, with the domain of integration restricted to \mathcal{D} . In this case, writing $\mathcal{T}_{\mathcal{D}}$ and $\mathbf{p}_{\mathcal{D}}$ to denote the finite element sub-mesh and polynomial degree distribution over \mathcal{D} , respectively, the finite element approximation is given by: Find $u_{\text{hp}}^* \in \mathcal{V}(\mathcal{T}_{\mathcal{D}}, \mathbf{p}_{\mathcal{D}})$ such that $u_{\text{hp}}^*|_{\partial\mathcal{D}} = \Pi g$ and

$$a_{\mathcal{D}}(u_{\text{hp}}^*, v) = \ell_{\mathcal{D}}(v) \quad \forall v \in \mathcal{V}_0(\mathcal{T}_{\mathcal{D}}, \mathbf{p}_{\mathcal{D}}),$$

where Πg denotes a piecewise polynomial approximation in $H^{1/2}(\partial\mathcal{D})$ of the Dirichlet datum g . Thereby, writing $\mathbf{E}_{\mathcal{D}}$ to denote the restriction of the energy functional \mathbf{E} over \mathcal{D} , i.e.,

$$\mathbf{E}_{\mathcal{D}}(u) := \frac{1}{2} a_{\mathcal{D}}(u, u) - \ell_{\mathcal{D}}(u),$$

we deduce the following identity:

$$\mathbf{E}_{\mathcal{D}}(u^*) - \mathbf{E}_{\mathcal{D}}(u_{\text{hp}}^*) = -\frac{1}{2} a_{\mathcal{D}}(u^* - u_{\text{hp}}^*, u^* - u_{\text{hp}}^*) + a_{\mathcal{D}}(u^*, u^* - u_{\text{hp}}^*) - \ell_{\mathcal{D}}(u^* - u_{\text{hp}}^*).$$

Employing integration by parts we deduce that

$$\begin{aligned} a_{\mathcal{D}}(u^*, u^* - u_{\text{hp}}^*) - \ell_{\mathcal{D}}(u^* - u_{\text{hp}}^*) &= \int_{\partial\mathcal{D}} \frac{\partial u^*}{\partial \mathbf{n}_{\mathcal{D}}} (u^* - u_{\text{hp}}^*) \, ds \\ &\equiv \int_{\partial\mathcal{D}} \mu'(\nabla u^*) \cdot \mathbf{n}_{\mathcal{D}} (u^* - u_{\text{hp}}^*) \, ds, \end{aligned}$$

where $\mathbf{n}_{\mathcal{D}}$ denotes the unit outward normal vector on the boundary $\partial\mathcal{D}$ of the domain \mathcal{D} , and $\mu'(\nabla u) = \nabla u$, cf. (4.2). Thereby,

$$(4.4) \quad \mathbb{E}_{\mathcal{D}}(u^*) - \mathbb{E}_{\mathcal{D}}(u_{\text{hp}}^*) = -\frac{1}{2} a_{\mathcal{D}}(u^* - u_{\text{hp}}^*, u^* - u_{\text{hp}}^*) + \int_{\partial\mathcal{D}} \mu'(\nabla u^*) \cdot \mathbf{n}_{\mathcal{D}} (u^* - u_{\text{hp}}^*) \, ds.$$

Stimulated by (4.4), we define the *local* energy functional $\tilde{\mathbb{E}}_{\mathcal{D}}(\cdot)$ by

$$(4.5) \quad \tilde{\mathbb{E}}_{\mathcal{D}}(v) := \mathbb{E}_{\mathcal{D}}(v) - \int_{\partial\mathcal{D}} \mu'(\nabla u^*) \cdot \mathbf{n}_{\mathcal{D}} v \, ds.$$

With this definition, we immediately deduce the following relationship between the error in the local energy functional and the error measured in terms of the local energy norm, namely,

$$\tilde{\mathbb{E}}_{\mathcal{D}}(u^*) - \tilde{\mathbb{E}}_{\mathcal{D}}(u_{\text{hp}}^*) = -\frac{1}{2} \|u^* - u_{\text{hp}}^*\|_{\mathbb{E}, \mathcal{D}}^2,$$

where, for $w \in H^1(\mathcal{D})$, we let $\|w\|_{\mathbb{E}, \mathcal{D}}^2 := a_{\mathcal{D}}(w, w)$. Moreover, if we consider the evaluation of the above local energy functional on each element κ , $\kappa \in \mathcal{T}$, then we note that the following consistency condition holds

$$\mathbb{E}(v) \equiv \sum_{\kappa \in \mathcal{T}} \tilde{\mathbb{E}}_{\kappa}(v).$$

Let us now write $u_{\text{hp}}^* \in \mathcal{V}(\mathcal{T}_{\mathcal{D}}, \mathbf{p}_{\mathcal{D}})$ and $u_{\text{hp}}^{*,'} \in \mathcal{V}(\mathcal{T}'_{\mathcal{D}}, \mathbf{p}'_{\mathcal{D}})$ to denote two finite element approximations to (4.3) based on employing the computational meshes $\mathcal{T}_{\mathcal{D}}$ and $\mathcal{T}'_{\mathcal{D}}$, respectively, with polynomial degree vectors $\mathbf{p}_{\mathcal{D}}$ and $\mathbf{p}'_{\mathcal{D}}$, respectively. Assuming the finite element space $\mathcal{V}(\mathcal{T}'_{\mathcal{D}}, \mathbf{p}'_{\mathcal{D}})$ represents an enrichment of the original one $\mathcal{V}(\mathcal{T}_{\mathcal{D}}, \mathbf{p}_{\mathcal{D}})$, we deduce that the expected reduction in the error in the energy functional defined over \mathcal{D} satisfies the equality

$$\begin{aligned} (4.6) \quad \tilde{\mathbb{E}}_{\mathcal{D}}(u_{\text{hp}}^*) - \tilde{\mathbb{E}}_{\mathcal{D}}(u_{\text{hp}}^{*,'}) &= (\tilde{\mathbb{E}}_{\mathcal{D}}(u^*) - \tilde{\mathbb{E}}_{\mathcal{D}}(u_{\text{hp}}^{*,'})) - (\tilde{\mathbb{E}}_{\mathcal{D}}(u^*) - \tilde{\mathbb{E}}_{\mathcal{D}}(u_{\text{hp}}^*)) \\ &= \frac{1}{2} \|u^* - u_{\text{hp}}^*\|_{\mathbb{E}, \mathcal{D}}^2 - \frac{1}{2} \|u^* - u_{\text{hp}}^{*,'}\|_{\mathbb{E}, \mathcal{D}}^2. \end{aligned}$$

Hence, by employing the modified local definition of the energy functional $\tilde{\mathbb{E}}_{\mathcal{D}}$ defined over the subdomain \mathcal{D} , we observe that the expected reduction in $\tilde{\mathbb{E}}_{\mathcal{D}}$ is directly related to the reduction in the energy norm of the error over \mathcal{D} , for the problem at hand, cf. (4.1). Moreover, we note that the above argument naturally holds for the finite element approximation of general second-order self-adjoint linear elliptic partial differential equations. The equality (4.6) serves as the motivation for the design of the proceeding *hp*-adaptive refinement algorithm for general convex minimisation problems, cf. below.




FIGURE 1. Local element patches in two-dimensions, when triangular elements are employed. (a) Original element κ (assumed to be an interior element); (b) Mesh patch $\mathcal{T}_{\kappa}^{\mathcal{N}}$, which consists of the element κ and its neighbours; (c) Mesh patch $\mathcal{T}_{\kappa,\text{ref}}^{\mathcal{N}}$ which is constructed based on isotropically refining κ (red refinement) and on a green refinement of its neighbours.

4.2. Competitive hp -refinement strategy. In this section, we develop an hp -adaptivity algorithm based on employing a competitive refinement strategy on each element κ in the computational mesh \mathcal{T} . The essential idea is to compute the maximal predicted energy reduction $\tilde{E}_{\kappa}(u_{\text{hp}}^*) - \tilde{E}_{\kappa}(u_{\kappa,\text{loc}}^*)$ on each element $\kappa \in \mathcal{T}$, where u_{hp}^* is the (global) finite element solution defined by (3.1), and $u_{\kappa,\text{loc}}^*$ is the (local) finite element approximation to the analytical solution u^* evaluated on a local patch of elements neighbouring κ , subject to a given p -/ hp -refinement. Employing the forthcoming notation $u_{\kappa,\text{loc}}^*$ will either represent $u_{\kappa,\text{p}}^* \in \mathcal{V}(\mathcal{T}_{\kappa}^{\mathcal{N}}, \mathbf{p}_{\text{p}})$, cf. (4.10), or $u_{\kappa,\text{hp}_i}^* \in \mathcal{V}(\mathcal{T}_{\kappa,\text{ref}}^{\mathcal{N}}, \mathbf{p}_{\text{hp}_i})$, $i = 1, \dots, N_{\kappa,\text{hp}}$, cf. (4.11), corresponding to either a local p - or hp -refinement of element κ , respectively. Elements with the largest maximal predicted decrease in the local energy functional are then appropriately refined. However, before we proceed, we first note that the boundary correction term included within the definition of the local energy functional $\tilde{E}_{\kappa}(\cdot)$, cf. (4.5) with \mathcal{D} replaced by κ , is not computable since it directly assumes knowledge of the unknown analytical solution u^* . With this in mind, we replace u^* by an approximate reference solution, cf. [14, 33]. However, in contrast to these citations, for the purposes of the current article we simply compute local reference solutions, rather than global ones. More precisely, given $\kappa \in \mathcal{T}$, we first construct the local mesh $\mathcal{T}_{\kappa}^{\mathcal{N}}$ comprising of κ and its immediate face-wise neighbours, cf. Fig. 1(b). Given $\mathcal{T}_{\kappa}^{\mathcal{N}}$, we then uniformly (red) refine element κ into n_k sub-elements; the introduction of any hanging nodes may then be removed by introducing additional (green) refinements, or alternatively, by simply uniformly refining all elements in the sub-mesh $\mathcal{T}_{\kappa}^{\mathcal{N}}$. For the purposes of the article, in two-dimensions, we exploit the




FIGURE 2. Polynomial degree distribution employed for the competitive hp -refinements: (a) One-dimension; (b) Two-dimensional triangular element.

former strategy, purely on the basis of reducing the number of degrees of freedom in the underlying local finite element space. Denoting the resulting finite element mesh by $\mathcal{T}_{\kappa, \text{ref}}^{\mathcal{N}}$, cf. Fig. 1(c), we construct the finite element space $\mathcal{V}(\mathcal{T}_{\kappa, \text{ref}}^{\mathcal{N}}, \mathbf{p}_{\text{ref}})$, where $\mathbf{p}_{\text{ref}}|_{\kappa'} = p_{\kappa} + 1$ for all $\kappa' \in \mathcal{T}_{\kappa, \text{ref}}^{\mathcal{N}}$. Writing $\bar{\mathcal{D}}(\kappa) = \bigcup_{\kappa' \in \mathcal{T}_{\kappa, \text{ref}}^{\mathcal{N}}} \bar{\kappa}'$, the elementwise reference solution may be computed as follows: Find $u_{\kappa, \text{ref}}^* \in \mathcal{V}(\mathcal{T}_{\kappa, \text{ref}}^{\mathcal{N}}, \mathbf{p}_{\text{ref}})$ such that $u_{\kappa, \text{ref}}^*|_{\partial \mathcal{D}(\kappa)} = u_{\text{hp}}^*|_{\partial \mathcal{D}(\kappa)}$ and

$$(4.7) \quad a_{\mathcal{D}(\kappa)}(u_{\kappa, \text{ref}}^*, v) = \ell_{\mathcal{D}(\kappa)}(v) \quad \forall v \in \mathcal{V}_0(\mathcal{T}_{\kappa, \text{ref}}^{\mathcal{N}}, \mathbf{p}_{\text{ref}}).$$

On the basis of the computed reference solution, we define the approximate local energy functional on κ , $\kappa \in \mathcal{T}$, as follows:

$$(4.8) \quad \tilde{\mathbf{E}}'_{\kappa}(v) := \mathbf{E}_{\kappa}(v) - \int_{\partial \kappa} \{\!\!\{ \mu'(\nabla u_{\kappa, \text{ref}}^*) \}\!\!\} \cdot \mathbf{n}_{\kappa} v \, ds,$$

where \mathbf{n}_{κ} denotes the unit outward normal vector to the boundary $\partial \kappa$ of κ , and $\{\!\!\{ \cdot \}\!\!\}$ denotes the average operator. More precisely, given two neighbouring elements κ^+ and κ^- , let x be an arbitrary point on the interior face given by $F = \partial \kappa^+ \cap \partial \kappa^-$. Given a vector-valued function \mathbf{q} which is smooth inside each element κ^{\pm} , we write \mathbf{q}^{\pm} to denote the traces of \mathbf{q} on F taken from within the interior of κ^{\pm} , respectively. Then, the average of \mathbf{q} at $x \in F$ is given by $\{\!\!\{ \mathbf{q} \}\!\!\} = \frac{1}{2}(\mathbf{q}^+ + \mathbf{q}^-)$. On a boundary face $F \subset \partial \Omega$, we set $\{\!\!\{ \mathbf{q} \}\!\!\} = \mathbf{q}^+$.

With the definition of $\tilde{\mathbf{E}}'_{\kappa}(\cdot)$ given in (4.8), we now outline the proposed competitive refinement strategy on element κ , $\kappa \in \mathcal{T}$. Firstly, we compute the predicted energy functional reduction when p -refinement is employed, i.e.,

$$(4.9) \quad \Delta \tilde{\mathbf{E}}'_{\kappa, \text{p}} := \tilde{\mathbf{E}}'_{\kappa}(u_{\text{hp}}^*) - \tilde{\mathbf{E}}'_{\kappa}(u_{\kappa, \text{p}}^*),$$

where $u_{\kappa, \text{p}}^*$ is the solution of the local finite element problem: Find $u_{\kappa, \text{p}}^* \in \mathcal{V}(\mathcal{T}_{\kappa}^{\mathcal{N}}, \mathbf{p}_{\text{p}})$ such that $u_{\kappa, \text{p}}^*|_{\partial \mathcal{D}(\kappa)} = u_{\text{hp}}^*|_{\partial \mathcal{D}(\kappa)}$ and

$$(4.10) \quad a_{\mathcal{D}(\kappa)}(u_{\kappa, \text{p}}^*, v) = \ell_{\mathcal{D}(\kappa)}(v) \quad \forall v \in \mathcal{V}_0(\mathcal{T}_{\kappa}^{\mathcal{N}}, \mathbf{p}_{\text{p}});$$

here, $\mathbf{p}_{\text{p}}|_{\kappa'} = p_{\kappa} + 1$ for all $\kappa' \in \mathcal{T}_{\kappa}^{\mathcal{N}}$.

Secondly, we also consider a sequence of competitive hp -refinements, such that the number of degrees of freedom associated with the finite element space defined over κ is identical to the case when pure p -refinement has been employed. Here,




FIGURE 3. Number of competitive hp -refinements, $N_{\kappa, hp}$, versus the local polynomial degree p_{κ} when a triangular element κ is isotropically refined.

for each element $\kappa \in \mathcal{T}$, we again exploit the same local mesh $\mathcal{T}_{\kappa, \text{ref}}^{\mathcal{N}}$ employed for the computation of the local reference solution $u_{\kappa, \text{ref}}^*$. Then for the elements which result from the isotropic refinement of κ , we employ local polynomial degrees p_{κ_i} , $i = 1, \dots, n_{\kappa}$; for the remaining elements stemming from the refinement of the neighbours of κ , we simply set the local polynomial degree equal to p_{κ} , cf. Fig. 2. For example, in one-dimension, following [14, 33], given an element κ with polynomial degree p_{κ} , an enrichment of $p_{\kappa} \rightarrow p_{\kappa} + 1$ gives rise to $p_{\kappa} + 2$ degrees of freedom associated with κ . On the other hand, we can now consider the case when κ is uniformly subdivided into two sub-elements κ_1 and κ_2 , i.e., $n_{\kappa} = 2$, with associated polynomial degrees p_{κ_1} and p_{κ_2} , respectively. To ensure that the number of degrees of freedom in the underlying hp -refined finite element space defined over κ_1 and κ_2 is identical to the case when pure p -enrichment is undertaken, we require that

$$p_{\kappa_1} + p_{\kappa_2} = p_{\kappa} + 1.$$

Hence, there are $N_{\kappa, hp} = p_{\kappa}$, hp -competitive refinements and one p -refinement in one-dimension.

In higher-dimensions, the construction of the competitive hp -refinements is undertaken in an analogous manner. For simplicity, we focus on the two-dimensional case when triangular elements are employed. Then for the elements which result from the isotropic refinement of κ , we employ local polynomial degrees p_{κ_i} , $i = 1, \dots, n_{\kappa} = 4$; as before, the local polynomial degree of the remaining elements stemming from the refinement of the neighbours of κ is set equal to p_{κ} . Let us signify the set of all such polynomial degree distributions on $\mathcal{T}_{\kappa, \text{ref}}^{\mathcal{N}}$ by $\mathfrak{P}_{\kappa, p_{\kappa}}$. Given that the full space of polynomials has been employed for the p -refinement, the number of degrees of freedom associated with κ is $\frac{1}{2}(p_{\kappa} + 2)(p_{\kappa} + 3)$. Then, for an arbitrary polynomial degree distribution $\{p_{\kappa_i}\}_{i=1}^4$ for the sub-elements $\{\kappa_i\}_{i=1}^4$

of κ , the number of degrees of freedom associated with κ is

$$6 + \sum_{i=1}^3 [\min(p_{\kappa_i}, p_{\kappa_4}) - 1 + 2(p_{\kappa_i} - 1)] + \frac{1}{2} \sum_{i=1}^4 (p_{\kappa_i} - 1)(p_{\kappa_i} - 2),$$

where we have assumed that κ_4 is the sub-element located at the interior of κ , cf. Fig. 2(b). Thereby, we select the set of hp -refinements which satisfy the condition

$$6 + \sum_{i=1}^3 [\min(p_{\kappa_i}, p_{\kappa_4}) - 1 + 2(p_{\kappa_i} - 1)] + \frac{1}{2} \sum_{i=1}^4 (p_{\kappa_i} - 1)(p_{\kappa_i} - 2) = \frac{1}{2} (p_{\kappa} + 2)(p_{\kappa} + 3).$$

Analogous expressions can also be determined for different element types, other kinds of refinement, e.g., anisotropic refinement, as well as in higher-dimensions. The precise number of competitive hp -refinements, denoted by $N_{\kappa, \text{hp}}$, is not possible to determine in a simple closed form expression; instead, $N_{\kappa, \text{hp}}$ can be precomputed for any polynomial order. To this end, in Fig. 3 we present the number of combinations of local polynomial degrees $\{p_{\kappa_i}\}_{i=1}^4$ with respect to p_{κ} in the above setting, i.e., for the case of isotropic refinement of a triangular element in two-dimensions. We notice that the number $N_{\kappa, \text{hp}}$ of possible p -configurations is, not surprisingly, growing as p_{κ} increases. In view of this observation we remark that, although the subsequent local discrete problems defined on each corresponding (patchwise) hp -finite element space, cf. (4.11) below, are extremely inexpensive to compute, and moreover are trivially parallelisable, from a practical point of view, it might be computationally beneficial to limit the number of samples to a certain preset maximum N_{\max} . For example, a random selection of N_{\max} samples may be considered, cf. Section 5 below; alternatively, a more sophisticated strategy selecting polynomial degree distributions with limited variations could be employed.

We now write $\mathcal{V}(\mathcal{T}_{\kappa, \text{ref}}^{\mathcal{N}}, \mathbf{p}_{\text{hp}_i})$, $i = 1, \dots, N_{\kappa, \text{hp}}$, to denote the finite element space based on employing the local (refined) mesh $\mathcal{T}_{\kappa, \text{ref}}^{\mathcal{N}}$ and some local polynomial degree distribution $\mathbf{p}_{\text{hp}_i} \in \mathfrak{P}_{\kappa, p_{\kappa}}$. Thereby, the following competitive hp -refinements may be defined: Find $u_{\kappa, \text{hp}_i}^* \in \mathcal{V}(\mathcal{T}_{\kappa, \text{ref}}^{\mathcal{N}}, \mathbf{p}_{\text{hp}_i})$ such that $u_{\kappa, \text{hp}_i}^*|_{\partial\mathcal{D}(\kappa)} = u_{\text{hp}}^*|_{\partial\mathcal{D}(\kappa)}$ and

$$(4.11) \quad a_{\mathcal{D}(\kappa)}(u_{\kappa, \text{hp}_i}^*, v) = \ell_{\mathcal{D}(\kappa)}(v) \quad \forall v \in \mathcal{V}_0(\mathcal{T}_{\kappa, \text{ref}}^{\mathcal{N}}, \mathbf{p}_{\text{hp}_i}),$$

for $i = 1, \dots, N_{\kappa, \text{hp}}$. For each local competitive hp -refinement, we compute the estimated local energy reduction

$$(4.12) \quad \Delta \tilde{E}'_{\kappa, \text{hp}_i} := \tilde{E}'_{\kappa}(u_{\text{hp}}^*) - \tilde{E}'_{\kappa}(u_{\kappa, \text{hp}_i}^*),$$

for $i = 1, \dots, N_{\kappa, \text{hp}}$. In this way, for each element $\kappa \in \mathcal{T}$, we may compute the maximum local predicted error reduction

$$(4.13) \quad \Delta \tilde{E}'_{\kappa, \max} = \max \left\{ \Delta \tilde{E}'_{\kappa, \text{p}}, \max_{i=1, \dots, N_{\kappa, \text{hp}}} \Delta \tilde{E}'_{\kappa, \text{hp}_i} \right\},$$

with $\Delta \tilde{E}'_{\kappa, \text{p}}$ from (4.9). Finally, we refine the set of elements $\kappa \in \mathcal{T}$ which satisfy the condition

$$(4.14) \quad \Delta \tilde{E}'_{\kappa, \max} > \theta \max_{\kappa \in \mathcal{T}} \Delta \tilde{E}'_{\kappa, \max},$$

where $0 < \theta < 1$ is a given parameter, cf. [14, 33]. On the basis of [14, 33], throughout this article, we set $\theta = 1/3$. The above competitive hp -refinement strategy is summarised in Algorithm 1.

Algorithm 1 Competitive hp -adaptive refinement procedure

-
- 1: Choose a coarse initial mesh \mathcal{T}_0 of Ω and a corresponding low-order starting polynomial degree vector \mathbf{p}_0 . Set $n = 0$.
 - 2: Solve (3.1) for $u_{\text{hp}}^* \in \mathcal{V}(\mathcal{T}_n, \mathbf{p}_n)$.
 - 3: **for** each element $\kappa \in \mathcal{T}_n$ **do**
 - 4: Construct the local reference mesh $\mathcal{T}_{\kappa, \text{ref}}^{\mathcal{N}}$.
 - 5: Compute the local finite element reference solution $u_{\kappa, \text{ref}}^* \in \mathcal{V}(\mathcal{T}_{\kappa, \text{ref}}^{\mathcal{N}}, \mathbf{p}_{\text{ref}})$ satisfying (4.7).
 - 6: Compute the local finite element p -enriched solution $u_{\kappa, \text{p}}^* \in \mathcal{V}(\mathcal{T}_{\kappa}^{\mathcal{N}}, \mathbf{p}_{\text{p}})$ satisfying (4.10), together with the corresponding predicted energy functional reduction $\Delta \tilde{\mathbf{E}}'_{\kappa, \text{p}}$, cf. (4.9).
 - 7: **for** $i = 1, \dots, N_{\kappa, \text{hp}}$ **do**
 - 8: Compute the local competitive hp -refined finite element solutions $u_{\kappa, \text{hp}_i}^* \in \mathcal{V}(\mathcal{T}_{\kappa, \text{ref}}^{\mathcal{N}}, \mathbf{p}_{\text{hp}_i})$ satisfying (4.11), together with their respective predicted energy functional reduction $\Delta \tilde{\mathbf{E}}'_{\kappa, \text{hp}_i}$ defined in (4.12).
 - 9: **end for**
 - 10: Compute the maximum local predicted error reduction $\Delta \tilde{\mathbf{E}}'_{\kappa, \text{max}}$, cf. (4.13).
 - 11: **end for**
 - 12: Determine the set of elements \mathcal{K}_n which are flagged for refinement, based on the criterion (4.14).
 - 13: Perform p - or hp -refinement on each $\kappa \in \mathcal{K}_n$ according to which refinement takes the maximum in (4.13). This results in a refined global finite element space $\mathcal{V}(\mathcal{T}_{n+1}, \mathbf{p}_{n+1})$.
 - 14: Set $n \leftarrow n + 1$, and goto Line 2.
 - 15: After sufficiently many iterations have been performed output the final solution $u_{\text{hp}}^* \in \mathcal{V}(\mathcal{T}_n, \mathbf{p}_n)$.
-

5. NUMERICAL EXAMPLES

In this section we present a series of numerical experiments to demonstrate the practical performance of the proposed hp -adaptive refinement strategy outlined in Algorithm 1. Throughout this section, for nonlinear problems, cf. Sections 5.2 & 5.3 below, we employ Newton's method to solve the resulting system of nonlinear equations with a termination tolerance of 1.0×10^{-12} ; within each inner (linear) iteration, we exploit the Multifrontal Massively Parallel Solver (MUMPS) [4–6].

5.1. Example 1: Linear Elliptic Problem. In this first example, we consider a one-dimensional problem defined over the domain $\Omega = (0, 1)$. Moreover, we set $\mu(u_x) = 1/2 \varepsilon u_x^2$, $\varepsilon > 0$, $g(u) = 1/2 u^2$, and $f(x) = 1$; this is equivalent to solving the linear elliptic boundary value problem:

$$-\varepsilon u_{xx}^* + u^* = 1, \quad x \in \Omega,$$

subject to homogeneous Dirichlet boundary conditions. We note that the analytical solution is given by

$$u^*(x) = \frac{e^{-1/\sqrt{\varepsilon}} - 1}{e^{1/\sqrt{\varepsilon}} - e^{-1/\sqrt{\varepsilon}}} e^{x/\sqrt{\varepsilon}} + \frac{1 - e^{1/\sqrt{\varepsilon}}}{e^{1/\sqrt{\varepsilon}} - e^{-1/\sqrt{\varepsilon}}} e^{-x/\sqrt{\varepsilon}} + 1.$$




FIGURE 4. Example 1. Comparison of the error with respect to the number of degrees of freedom: (a) $|E(u^*) - E(u_{hp}^*)|$; (b) $\|u^* - u_{hp}^*\|_E$; (c) $\|u^* - u_{hp}^*\|_{L^2(\Omega)}$. (d) hp -Mesh distribution after 9 adaptive refinements.

In particular, for $0 < \varepsilon \ll 1$, the analytical solution u^* contains boundary layers in the vicinity of $x = 0$ and $x = 1$, cf. [37]; as in [37], we set $\varepsilon = 10^{-5}$.

In Fig. 4 we illustrate the performance of the proposed hp -adaptive algorithm, cf. Algorithm 1, based on a starting mesh consisting of 4 elements, with the initial polynomial degree $\mathbf{p} = [1, 1, 1, 1]$. Here, we have plotted the error in the underlying energy functional E , together with the energy norm $\|\cdot\|_E$ and $L^2(\Omega)$ norm of the error, with respect to the total number of degrees of freedom employed within the finite element space $\mathcal{V}(\mathcal{T}, \mathbf{p})$, on a linear-log scale; here,

$$\|v\|_E^2 = \int_0^1 (\varepsilon v_x^2 + v^2) dx.$$

From Fig. 4(a), (b), & (c), we observe, that after an initial transient, the convergence lines for each error measure become (on average) straight, thereby indicating exponential convergence of the quantities $|E(u^*) - E(u_{hp}^*)|$, $\|u^* - u_{hp}^*\|_E$, and $\|u^* - u_{hp}^*\|_{L^2(\Omega)}$, respectively, as $\mathcal{V}(\mathcal{T}, \mathbf{p})$ is adaptively enriched. Finally, in Fig. 4(d) we show the hp -mesh distribution after 9 adaptive refinements. Here, we observe




FIGURE 5. Example 2. Comparison of the error with respect to the third root of the number of degrees of freedom: (a) $|E(u^*) - E(u_{hp}^*)|$; (b) $\|u^* - u_{hp}^*\|_{H^1(\Omega)}$; (c) $\|u^* - u_{hp}^*\|_{L^2(\Omega)}$.

that the algorithm clearly identifies the location of the boundary layers present in the analytical solution u^* ; indeed, in these regions, local subdivision of the mesh has first been employed, followed by subsequent p -enrichment, cf. [37].

5.2. Example 2: Strongly monotone quasilinear PDE. In this second example, we let Ω be the L-shaped domain $(-1, 1)^2 \setminus [0, 1) \times (-1, 0]$, and set

$$\mu(\nabla u) = \frac{1}{2} \left(|\nabla u|^2 - e^{-|\nabla u|^2} \right).$$

Thereby, the corresponding Euler–Lagrange equation for the underlying minimisation problem corresponds to the strongly monotone quasilinear PDE given by:

$$(5.1) \quad -\nabla \cdot \left(\left(1 + e^{-|\nabla u^*|^2} \right) \nabla u^* \right) = f, \quad \text{in } \Omega.$$

We select f and appropriate inhomogeneous Dirichlet boundary conditions so that the analytical solution to (5.1) is given by

$$u = r^{2/3} \sin\left(\frac{2}{3}\varphi\right),$$

where (r, φ) denote the system of polar coordinates, cf. [13, 23], for example.

In Fig. 5 we present the convergence history of the error in the computed energy functional E , together with $\|u^* - u_{hp}^*\|_{H^1(\Omega)}$, and $\|u^* - u_{hp}^*\|_{L^2(\Omega)}$, as the finite element space is hp -adaptively refined. On a linear-log scale (where the horizontal axis measures the third root of the total number of the degrees of freedom, cf. [32]), we again observe exponential rates of convergence, in the sense that asymptotically the convergence lines become roughly straight. In addition, in Fig. 5 we also present analogous results in the case when a Monte Carlo (MC) approach is employed to limit the number N_{\max} of hp -refinement samples considered on each element. More precisely, we randomly select samples based on employing $N_{\max} = 10$ and $N_{\max} = 15$; in each case two typical realisations are presented. Here, we observe a slight degradation of the rate of convergence in each of the above error quantities as our hp -refinement procedure progresses, as we would expect; however, in each case exponential convergence is retained when this simple selection principle is exploited. As noted in Section 4.2 more sophisticated selection principles may also be employed.

The final hp -mesh distribution is depicted in Fig. 6; here, we see that the computational mesh has been largely refined in the vicinity of the re-entrant corner located at the origin. In addition, we see that the polynomial degrees have been increased away from the origin, since the underlying analytical solution is smooth in this region. In particular, we observe that the refinement algorithm has generated an hp -mesh distribution which is symmetric with respect to the line $x_2 = -x_1$.

5.3. Example 3: p -Laplacian. In this final example, for $p > 1$, we consider the p -Laplacian problem

$$(5.2) \quad -\nabla \cdot (|\nabla u^*|^{p-2} \nabla u^*) = f, \quad \text{in } \Omega = (0, 1)^2,$$

subject to inhomogeneous Dirichlet boundary conditions. We point out that in this setting, (5.2) corresponds to the Euler-Lagrange equation for the energy minimisation problem

$$\min_{u \in W_0^{1,p}(\Omega)} \left\{ \frac{1}{p} \int_{\Omega} |\nabla u|^p dx - \int_{\Omega} f u dx \right\};$$

i.e., we have $\mu(\nabla u) = 1/p |\nabla u|^p$ and $g = 0$. We select f , and impose suitable inhomogeneous Dirichlet boundary conditions, so that the analytical solution of (5.2) is given by

$$u^*(x) = r^\alpha, \quad \alpha > 0.$$

As in [1], throughout this section, we set $p = 3$ and $\alpha = 3/4$, which implies that $u^* \in W^{\beta-\epsilon, 3}(\Omega)$, where $\beta = 13/6$ and $\epsilon > 0$ is arbitrarily small.

In Fig. 7 we plot $|E(u^*) - E(u_{hp}^*)|$, $\|u^* - u_{hp}^*\|_{W^{1,3}(\Omega)}$, and $\|u^* - u_{hp}^*\|_{L^3(\Omega)}$, with respect to the third root of the number of degrees of freedom in $\mathcal{V}(\mathcal{T}, p)$. As in the previous examples, we again observe exponential convergence of each of the above error measures, as the finite element space is hp -adaptively modified. We also consider the case when $N_{\max} = 30$ random samples are selected; in particular, here we present two different Monte Carlo realisations, both with $N_{\max} = 30$. As in the previous example, we again see that exponential convergence of each of the above error quantities is retained, though the rate of convergence is inferior when compared to the case when all potential trial hp -refinements are considered. The final hp -mesh distribution is shown in Fig. 8; as in the previous examples, the adaptive algorithm clearly identifies the location of the singularity present within the analytical solution u^* , whereby h -refinement is undertaken.




FIGURE 6. Example 2. (a) hp -Mesh distribution after 18 adaptive refinements; (b) Zoom of (a).

6. CONCLUSIONS

In this article, we have proposed a novel hp -adaptive refinement procedure for application to the finite element approximation of convex variational problems. In particular, the underlying adaptive algorithm exploits a competitive refinement technique which seeks to maximise the decrease in the elemental contribution to the total energy based on employing local p - and hp -enrichments of the finite element space. Whilst our approach has been successfully applied to a range of second-order quasilinear problems in both one- and two-dimensions, we emphasise that it is immediately extensible to more general variational-based PDE problems. Future work will be concerned with exploiting anisotropic hp -mesh adaptation.




FIGURE 7. Example 3. Comparison of the error with respect to the third root of the number of degrees of freedom: (a) $|E(u^*) - E(u_{hp}^*)|$; (b) $\|u^* - u_{hp}^*\|_{W^{1,3}(\Omega)}$; (c) $\|u^* - u_{hp}^*\|_{L^3(\Omega)}$.

REFERENCES

1. M. Ainsworth and D. Kay, *The approximation theory for the p-version finite element method and application to non-linear elliptic PDEs*, Numer. Math. **82** (1999), 351–388.
2. M. Ainsworth and J.T. Oden, *A posteriori error estimation in finite element analysis*, Series in Computational and Applied Mathematics, Elsevier, 1996.
3. M. Ainsworth and B. Senior, *An adaptive refinement strategy for hp-finite element computations*, Appl. Numer. Math. **26** (1998), no. 1–2, 165–178.
4. P. R. Amestoy, I. S. Duff, J. Koster, and J.-Y. L'Excellent, *A fully asynchronous multifrontal solver using distributed dynamic scheduling*, SIAM Journal on Matrix Analysis and Applications **23** (2001), no. 1, 15–41.
5. P. R. Amestoy, I. S. Duff, and J.-Y. L'Excellent, *Multifrontal parallel distributed symmetric and unsymmetric solvers*, Comput. Methods Appl. Mech. Eng. **184** (2000), 501–520.
6. P. R. Amestoy, A. Guermouche, J.-Y. L'Excellent, and S. Pralet, *Hybrid scheduling for the parallel solution of linear systems*, Parallel Computing **32** (2006), no. 2, 136–156.
7. I. Babuška and B. Q. Guo, *Regularity of the solution of elliptic problems with piecewise analytic data. Part I. Boundary value problems for linear elliptic equation of second order*, SIAM J. Math. Anal. **19** (1988), 172–203.
8. I. Babuška and M. Suri, *The hp-version of the finite element method with quasiuniform meshes*, RAIRO Anal. Numér. **21** (1987), 199–238.




FIGURE 8. Example 3. (a) hp -Mesh distribution after 23 adaptive refinements; (b) Zoom of (a).

9. ———, *The treatment of nonhomogeneous Dirichlet boundary conditions by the p -version of the finite element method*, Numer. Math. **55** (1989), 97–121.
10. ———, *The p and h - p versions of the finite element method, basic principles and properties*, SIAM Review **36** (1994), 578–632.
11. R. Becker and R. Rannacher, *An optimal control approach to a-posteriori error estimation in finite element methods*, Acta Numerica (A. Iserles, ed.), Cambridge University Press, 2001, pp. 1–102.
12. C. Bernardi, N. Fiétier, and R. G. Owens, *An error indicator for mortar element solutions to the Stokes problem*, IMA J. Numer. Anal. **21** (2001), no. 4, 857–886.
13. S. Congreve, P. Houston, and T. P. Wihler, *Two-grid hp -version discontinuous Galerkin finite element methods for second-order quasilinear elliptic PDEs*, J. Sci. Comput. **55** (2013), no. 2, 471–497.
14. L. Demkowicz, *Computing with hp -adaptive finite elements. Vol. 1*, Chapman & Hall/CRC Applied Mathematics and Nonlinear Science Series, Chapman & Hall/CRC, Boca Raton, FL, 2007, One and two dimensional elliptic and Maxwell problems.

15. L. Demkowicz, W. Rachowicz, and Ph. Devloo, *A fully automatic hp-adaptivity*, J. Sci. Comput. **17** (2002), no. 1-4, 117–142.
16. W. Dörfler and V. Heuveline, *Convergence of an adaptive hp finite element strategy in one space dimension*, Appl. Numer. Math. **57** (2007), no. 10, 1108–1124.
17. T. Eibner and J. M. Melenk, *An adaptive strategy for hp-FEM based on testing for analyticity*, Comput. Mech. **39** (2007), no. 5, 575–595.
18. K. Eriksson, D. Estep, P. Hansbo, and C. Johnson, *Introduction to adaptive methods for differential equations*, Acta Numerica (A. Iserles, ed.), Cambridge University Press, 1995, pp. 105–158.
19. E. H. Georgoulis, E. Hall, and P. Houston, *Discontinuous Galerkin methods on hp-anisotropic meshes II: A posteriori error analysis and adaptivity*, Appl. Numer. Math. **59**(9) (2009), 2179–2194.
20. S. Giani and P. Houston, *Anisotropic hp-adaptive discontinuous Galerkin finite element methods for compressible fluid flows*, Int. J. Numer. Anal. Model. **9** (2012), no. 4, 928–949.
21. P. Houston and E. Süli, *Adaptive finite element approximation of hyperbolic problems*, Error Estimation and Adaptive Discretization Methods in Computational Fluid Dynamics. Lect. Notes Comput. Sci. Engrg. (T. Barth and H. Deconinck, eds.), vol. 25, Springer, 2002, pp. 269–344.
22. P. Houston and E. Süli, *A note on the design of hp-adaptive finite element methods for elliptic partial differential equations*, Comput. Methods Appl. Mech. Engrg. **194**(2-5) (2005), 229–243.
23. P. Houston, E. Süli, and T. P. Wihler, *A posteriori error analysis of hp-version discontinuous Galerkin finite element methods for second-order quasi-linear PDEs*, IMA J. Numer. Anal. **28** (2007), no. 2, 245–273.
24. G. E. Karniadakis and S. Sherwin, *Spectral/hp finite element methods in cfd*, Oxford University Press, 1999.
25. C. Mavriplis, *Adaptive mesh strategies for the spectral element method*, Comput. Methods Appl. Mech. Engrg. **116** (1994), no. 1-4, 77–86, ICOSAHOM'92 (Montpellier, 1992).
26. J. M. Melenk and B. I. Wohlmuth, *On residual-based a posteriori error estimation in hp-FEM*, Adv. Comp. Math. **15** (2001), 311–331.
27. W. F. Mitchell and M. A. McClain, *A comparison of hp-adaptive strategies for elliptic partial differential equations*, ACM Transactions on Mathematical Software (TOMS) **41** (2014), 2:1–2:39.
28. J. T. Oden, A. Patra, and Y. S. Feng, *An hp-adaptive strategy*, Adaptive, Multilevel, and Hierarchical Computational Strategies, vol. 157, ASME Publication, New York, 1992, pp. 23–26.
29. D. Pardo and L. Demkowicz, *Integration of hp-adaptivity and a two-grid solver for elliptic problems*, Comput. Methods Appl. Mech. Engrg. **195** (2006), 674–710.
30. P. H. Rabinowitz, *Minimax methods in critical point theory with applications to differential equations*, CBMS Regional Conference Series in Mathematics, vol. 65, Published for the Conference Board of the Mathematical Sciences, Washington, DC; by the American Mathematical Society, Providence, RI, 1986.
31. W. Rachowicz, J. T. Oden, and L. Demkowicz, *Toward a universal hp-adaptive finite element strategy. Part 3: Design of hp meshes*, Comput. Methods Appl. Mech. Engrg. **77** (1989), 181–212.
32. C. Schwab, *p- and hp-FEM – Theory and application to solid and fluid mechanics*, Oxford University Press, Oxford, 1998.
33. P. Solin, K. Segeth, and I. Dolezel, *Higher-order finite element methods*, Studies in advanced mathematics, Chapman & Hall/CRC, Boca Raton, London, 2004.
34. B. Szabó and I. Babuška, *Finite element analysis*, J. Wiley & Sons, New York, 1991.
35. J. Valenciano and R. G. Owens, *An h-p adaptive spectral element method for Stokes flow*, Appl. Numer. Math. **33** (2000), no. 1-4, 365–371.
36. R. Verfürth, *A review of a posteriori error estimation and adaptive mesh-refinement techniques*, B.G. Teubner, Stuttgart, 1996.
37. T. P. Wihler, *An hp-adaptive strategy based on continuous Sobolev embeddings*, J. Comput. Appl. Math. **235** (2011), 2731–2739.

38. E. Zeidler, *Nonlinear functional analysis and its applications. III*, Springer-Verlag, New York, 1985, Variational methods and optimization, Translated from the German by L. F. Boron. MR 768749 (90b:49005)

SCHOOL OF MATHEMATICAL SCIENCES, UNIVERSITY OF NOTTINGHAM, UNIVERSITY PARK, NOTTINGHAM, NG7 2RD, UK

E-mail address: `Paul.Houston@nottingham.ac.uk`

MATHEMATISCHES INSTITUT, UNIVERSITÄT BERN, SIDLERSTRASSE 5, CH-3012 BERN, SWITZERLAND

E-mail address: `wihler@math.unibe.ch`